



YB2 Type Flameproof Electric Motor for Hazardous Area (Ex-Marking ExdII BT4 ExdII CT4)

MOUNTING IMB3

Type	Poles	H	A	B	C	D	E	F	G	GD	K	AB	AD	AC	HD	AA	BB	HA	L
63	2-10 Poles	63	100	80	40	11	23	4	8.5	5	7	125	165	150	230	25	110	8	241
71	2-10 Poles	71	112	90	45	14	30	5	11	6	7	140	165	155	250	28	114	8	267
80	2-10 Poles	80	125	100	50	19	40	6	5.5	6	10	165	175	165	300	34	130	10	320
90S	2-10 Poles	90	140	100	56	24	50	8	20	7	10	180	175	180	320	36	135	14	355
90L	2-10 Poles	90	140	125	56	24	50	8	20	7	10	180	175	180	320	36	160	14	380
100L	2-10 Poles	100	160	140	63	28	60	8	24	7	12	200	180	205	345	43	180	14	435
112M	2-10 Poles	112	190	140	70	28	60	8	24	8	12	245	175	230	360	50	180	16	445
132S	2-10 Poles	132	216	140	89	38	80	10	33	8	12	280	185	270	420	60	190	18	490
132M	2-10 Poles	132	216	178	89	38	80	10	33	8	12	280	185	270	420	60	230	18	520
160M	2-10 Poles	160	254	210	108	42	110	12	37	8	15	330	208	330	485	70	260	25	645
160L	2-10 Poles	160	254	254	108	42	110	12	37	8	15	330	208	330	485	70	310	25	685
180M	2-10 Poles	180	279	241	121	48	110	14	42.5	9	15	335	202	360	525	70	311	22	720
180L	2-10 Poles	180	279	279	121	48	110	14	42.5	9	15	335	202	360	525	70	349	22	740
200L	2-10 Poles	200	318	305	133	55	110	16	49	10	19	390	250	400	645	70	370	25	805
225S	2 Poles	225	356	286	149	55	110	16	49	11	19	435	250	450	690	75	355	28	865
225S	4-10 Poles	225	356	286	149	60	140	18	53	11	19	435	250	450	690	75	355	28	865
225M	2 Poles	225	356	311	149	55	110	16	49	10	19	435	250	450	690	75	380	28	860
225M	4-10 Poles	225	356	311	149	60	140	18	53	11	19	435	250	450	690	75	380	28	890
250M	2-10 Poles	250	406	349	168	60	140	18	53	11	24	490	275	500	720	80	420	30	945
280S	2 Poles	280	457	368	190	65	140	18	58	11	24	545	300	560	790	85	438	35	1010
280S	4-10 Poles	280	457	368	190	75	140	20	67.5	12	24	545	300	560	790	85	438	35	1010
280M	2 Poles	280	457	419	190	65	140	18	58	11	24	545	300	560	790	85	489	35	1060
280M	4-10 Poles	280	457	419	190	75	140	20	67.5	12	24	545	300	560	790	85	489	35	1060
315S	2 Poles	315	508	406	216	65	140	18	58	11	28	640	400	630	1020	130	551	38	1300
315S	4-10 Poles	315	508	406	216	80	170	22	71	14	28	640	400	630	1020	130	551	38	1330
315M	2 Poles	315	508	457	216	65	140	18	58	11	28	640	400	630	1020	130	602	38	1380
315M	4-10 Poles	315	508	457	216	80	170	22	71	14	28	640	400	630	1020	130	602	38	1410
315L	2 Poles	315	508	508	216	65	140	18	58	11	28	640	400	630	1020	130	653	38	1470
315L	4-10 Poles	315	508	508	216	80	170	22	71	14	28	640	400	630	1020	130	653	38	1500
355S	2 Poles	355	610	500	254	75	140	20	67.5	12	28	740	500	750	1080	150	740	40	1530
355S	4-10 Poles	355	610	500	254	95	170	25	86	14	28	740	500	750	1080	150	740	40	1560
355M	2 Poles	355	610	560	254	75	140	20	67.5	12	28	740	500	750	1080	150	740	40	1530
355M	4-10 Poles	355	610	560	254	95	170	25	86	14	28	740	500	750	1080	150	740	40	1560
355L	2 Poles	355	610	630	254	75	140	20	67.5	12	28	740	500	750	1080	150	810	40	1600
355L	4-10 Poles	355	610	630	254	95	170	25	86	14	28	740	500	750	1080	150	810	40	1630